

Mood Line 55/40 - Desk element

Well-being and efficiency at the workplace

Thanks to their outstanding acoustic properties, the AOS Mood Line walls ensure the best possible room acoustics and thus well-being and efficiency in the workplace. The desk-mounted elements are available in the heights 480 and 680 mm, the behind-desk elements in the heights 680, 800 and 1000 mm. With 8 standard widths, up to 2000 mm and moreover also in individual customization, can be responded to any desk size and arrangement. Whether Mood Line 55 with a total thickness of 55 mm or Mood Line 40, the desk elements are available in both design versions. Fully upholstered, with rounded corners in a radius of 20 mm or in the rigid angular version with internal profiled material, alternatively powder-coated. Available in 17 fabric collections - divided into 5 price groups - and with more than 500 colours, they are sources of inspiration for a creative and at the same time highly sound-absorbing room structure. There are 10 fabric collections available as quilting fabric.

Soundproof with individual desk connection

Free Line desk elements are available in 3 variants. As a desk add-on element, positioned on the rear edge of the table flush with the lower edge of the desk top, as a desk top element, positioned on the desk flush with the rear edge of the desk and as a rear desk element positioned on the rear edge of the desk with a hanging overhang of at least 180 mm. It is attached to the desk using a clamp, suitable for board thicknesses of 19 to 25 mm.



Daten Mood Line 55/40 Desk element

Wall thickness 55 mm (alternatively 40 mm)

Fully upholstered design - alternatively with internal profiles fabric-covered or powder-coated RAL 7016 anthracite gray and RAL 9006 white aluminum

Connection options using table clamps:
one-sided, two-sided, rear table

Desk clamps, powder-coated
RAL 7016 anthracite gray / RAL 9006 white aluminum

Highly sound-absorbing according to DIN EN ISO 354

Filler B1 flame retardant according to DIN 4102-1

Filler Standard 100 by OEKO-TEX®

Optional organizational accessories

Optionally with an acoustic filling
made of sheep's wool - 100% sustainable

Detail view



Desk-mounted element with organisational accessory



Desk-mounted element single-sided



Desk-mounted element



Behind-desk element




Behind-desk element divided




Behind-desk element with organisational accessory


Connector elements



one-side



two-side



rear table

Mood Line 55 mm

Sound absorption coefficient
ap per DIN EN ISO 354

125 Hz	ap 0,33
250 Hz	ap 0,59
500 Hz	ap 0,77
1000 Hz	ap 0,87
2000 Hz	ap 0,94
4000 Hz	ap 0,96

Rated sound absorption coefficient
aw 0,80 (H). DIN EN ISO 354 test certificate

Mood Line 40 mm

Sound absorption coefficient
ap per DIN EN ISO 354

125 Hz	ap 0,21
250 Hz	ap 0,37
500 Hz	ap 0,60
1000 Hz	ap 0,69
2000 Hz	ap 0,75
4000 Hz	ap 0,88

Rated sound absorption coefficient
aw 0,65 (H). DIN EN ISO 354 test certificate